

## EC Declaration of Performance Murfor® Compact A - 80

### CUSTOMER INFORMATION

1. Unique identification code of the product : Murfor® Compact A - 80
2. Intended use :  
Ancillary components Masonry : Bed joint reinforcement for "Structural Use" in masonry-horizontal joints - as covered in the scope of ETA 18/0316: v2
3. Manufacturer : NV BEKAERT SA - Bekaertstraat 2, B-8550 Zwevegem, Belgium.
5. System of assessment and verification of constancy of performance of the construction product :  
System n°3
- 6b. European Assessment Document : EAD n°. 170008-00-0604 - 2018  
European Technical Assessment : ETA n° 18/0316 : version 2  
Technical Assessment Body : UBAtc - Lombardstraat/Rue Lombard 42 - 1000 Brussels  
Notified Labs :  
TZUS - Technicky a zkusebni ustav stavebni, Praha - Czech Republic;  
TSUS - Technicky a skusobny ustav stavebny, Bratislava - Slovakia;  
VUCHV - Vyskumny ustav chemickych vlakien, Svit - Slovakia.
7. Declared performance : the essential characteristics per product type are listed in table 1.

The performance of the products identified above and listed in table 1, is in conformity with the set of declared performances from point 7.

This declaration of performance is issued, in accordance with regulation (EU) N°305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by :

Tom Hautekiet, Vice President Building Products, NV BEKAERT SA.

## EC Declaration of Performance Murfor® Compact A - 80

### CUSTOMER INFORMATION

Addendum to pt 7. Declared Performance on essential characteristics – see table 1 in accordance with ETA 18/0316: v2

| Table 1: Declaration on essential characteristics                   |   |
|---|---|
| Product type  | Murfor® Compact A - 80  |
| Width [w] + tol (mm)  | 80 ± 5  |
| Intended use  | bed joint reinforcement for 'structural use' in masonry, with thin layer mortar or normal purpose mortar and with AAC blocks. |
| Exposure conditions   | MX1   |
| Total Steel Section (mm <sup>2</sup> )<br>(cord section x n° cords) | 9.66 - (0.69 x 14)  |
| Material/coating reference - Longitudinal steelcord                 | R 20  |
| Yield Strenght (N/mm <sup>2</sup> )                                 | 1770  |
| Ductility class - Agt % - tensile/yield                             | LOW - ≥ 2.2 - >1.08   |
| Steel Wire diameter [c] (mm) x n° wires in cord                     | 0.54 x 3  |
| Profile height (mm)   | 1.75 ± 0.2  |
| Pitch [b] + tol. (mm)   | 33 ± 3.3  |
| Pitch between cords [f]-[e] (mm)                                    | 10 - 5  |
| Roll Length [l] + tol. (m)  | 30 ± 0.45   |
| Transverse Roving wire, Tensile Force (N) - Total Elongation (%)    | 380 - 1.4   |
| Bond strength (kN)  | 9.33  |
| Bond & Anchorage length (mm)  | 250   |
| Masonry units and mortar for stated bond & anchorage length         | fb ≥ 3 N/mm <sup>2</sup> and fm ≥ 10 N/mm <sup>2</sup>  |

Disclaimer: This Customer Information shall not constitute a guarantee for any specific product features. Final determination of suitability of this material is the sole responsibility of the user